IWAN (DE) Applicant(s): BOSCH GN Requested	
Inventor(s): KLUTH CA IWAN (DE) Applicant(s): BOSCH GN Requested	RSTEN (DE); TORNO OSKAR (DE); FRANKE STEFFEN (DE); SURJADI B AUML UERLE MICHAEL (DE); H AUML MING WERNER (DE) IBH ROBERT (US)
IWAN (DE) Applicant(s): BOSCH GN Requested	; B AUML UÉRLE MICHAEL (DÈ); Ĥ AUML MING WERNÈR (ĎE) IBH ROBERT (US)
Requested	
	12861
Patent: DE197	
Application Number: US1999038	31711 19991206
Priority Number (s): DE1997101	12861 19970327; WO1997DE02780 19971128
IPC Classification: F02B33/00	
EC Classification: F02D23/00	, <u>F02D41/00D4</u>
Equivalents: CN1095032	2B, CN1238027, ☐ <u>EP0979351</u> (WO9844252), <u>B1</u> , JP2001518162T, 4252
Abstract	
To achieve a very sturdy automatic control of the boost pressure, the integration of system deviation of the boost pressure, which is carried out by an integrator, is limited to a predefinable limiting value. Limiting value is composed of a basic value and a correction value superimposed upon it. Correction value is determined adaptively as a function of speed, a plurality of speed ranges being predefined. Adapted correction value can be increased or reduced stepwise, which mainly depends on whether the integral-action component of the manipulated variable for the boost pressure is smaller or greater than the current limiting value Data supplied from the esp@cenet database - 12	